81X CHAIN, 3939-B4 & M900




The Many Faces of 81X

Why choose one over the other? 81X is at the heart of every modern sawmill operation. This versatile chain is available in many grades of quality. At Tsubaki we are proud to offer three tiered levels of 81X quality:

Tier	Key Features	Key Applications			
81X Econo	An economical version that meets the general need of non-timed	Non-Timed Conveyors:			
	sawmill applications.	Transfers			
81X Premium	Building upon the strength of the 81X design, Premium offers better	Multi-strand Timed Conveyors:			
	performance on multi-strand timed conveyors where relative length	Scanner			
	tolerance and rate of stretch is critical.	Trimmer			
	Improved material & heat treatment	Drop Sorter			
	 Precision and consistency of fabrication & assembly 				
81X Lambda ¹	Oil impregnated sintered metal bushing for lube-free operation.	Multi-strand Timed Conveyors:			
	 7-14 times longer life than unlubricated chain 	Drop Sorter			
	 Same precision of material, heat treatment, fabrication 	Trimmer			
	and assembly as 81X Premium.	Scanner			
		Any application where contamination			
		of the product must be avoided			

1 Note that 81X Lambda chain has a slighter wider profile than Premium or Econo.

81X Chain




				LINK Flate		FIII						
			Width									
			Between								Average	
		Roller	Inner Link								Tensile	Approx.
	Pitch	Diameter	Plates	Thickness	Thickness	Height	Diameter	Length	Length	Length	Strength	Weight
Chain Number	Р	R	W	T1	T ₂	Η̈́	D	L1+ L2	L1	L2	(lbs.)	(lbs./ft.)
81X Econo	2.609	0.906	1.060	0.157	0.157	1.125	0.437	2.063	0.951	1.112	24,000	2.42
81X Premium	2.609	0.906	1.060	0.157	0.157	1.125	0.437	2.063	0.951	1.112	24,000	2.42
81X Premium NEP	2.609	0.906	1.060	0.157	0.157	1.125	0.437	2.063	0.951	1.112	24,000	2.42
81XHD Econo	2.609	0.906	1.060	0.220	0.315	1.260	0.437	2.536	1.181	1.355	42,000	4.12
81XHD Premium	2.609	0.906	1.060	0.220	0.315	1.260	0.437	2.536	1.181	1.355	42,000	4.12
81X Lambda	2.609	0.906	1.060	0.157	0.189	1.125	0.437	2.146	0.998	1.148	24,000	2.42
81XSS	2.609	0.906	1.060	0.157	0.157	1.125	0.437	2.063	0.951	1.112	11,000	2.42

3939-B4

3939-B4 chain is an 8" pitch version of 81X chain and is used for lumber conveying. It is typically used in drop sorter applications. Lumber is conveyed using J-bar attachments on the chain. Tsubaki can install the J-bars on the chain. Tsubaki can also supply sprockets to work with 3939-B4 chain. Please contact Tsubaki Technical Support for more information.



When choice really matters



M900

